

Town of Croghan
New Town Road Specifications

1. 50 ft RIGHT OF WAY
2. Road must be excavated to a width of 20 ft and 4 ft shoulders.
3. Built up with suitable material to provide adequate drainage and improve snow removal conditions.
4. Road bed must have not less than 18 inches of gravel, topped with 6 inches of 1 inch and minus limestone crusher run.
5. All brush to be removed, back slopes to be graded.
6. Ditches and sluices installed where necessary.
7. Roads must have a bituminous top at least 20 feet wide using 2" cold mix matt with oil and stone finish. 1as.
8. Roads to be approved by Town Superintendent and Town Board.
9. Specifications may be changed as deemed necessary by the Town Superintendent and Board.
10. Dedication by Town Board in accordance with the Town Highway Superintendents Manual.

State of New York
County of Lewis
Town of Croghan – Regular Meeting – December 15, 2014

22-5. RESOLUTION #119-2014

NEW TOWN ROAD SPECIFICATIONS – POLICY NO. 3

On motion made by Councilman Burriss, seconded by Councilman Farney, the following resolution was

ADOPTED – AYES 4 A. Lehman, Burriss, Farney, J. Lehman (ABSENT 1 Monnat)

NAYS 0

Resolved that the New Town Road Specifications – Policy No. 3 be approved as presented.